

मंगलुर रिफाइनरी एण्ड पेट्रोकेमिकल्स लिमिटेड

MANGALORE REFINERY AND PETROCHEMICALS LIMITED

अनुसूची 'अ' के अंतर्गत भारत सरकार का उद्यम SCHEDULE 'A' GOVT. OF INDIA ENTERPRISE. (ऑयल एण्ड नेचुरल गैंस कॉरपोरेशन लिमिटेड की सहायक कंपनी A SUBSIDIARY OF OIL AND NATURAL GAS CORPORATION LIMITED) सीआईएन/CIN : L23209KA1988GOI008959

पंजीकृत कार्भालय : कुत्तेतूर पोस्ट, वाया काटीपल्ला मंगलूरु -575 030 (भारत) दूरभाष 0824-2270400, फैक्स: 0824-2271404, E-mail:mrplmlr@mrpl.co.in Regd. Office : Kuthethoor P.O. Via Katipalla, Mangaluru - 575 030 (India) Tel. : 0824-2270400 Fax : 0824-2271404 Website : www.mrpl.co.in

आई.एस.ओ. 9001, 14001 एवं 50001 प्रमाणित कंपनी AN ISO 9001, 14001 AND 50001 CERTIFIED COMPANY

L/MS/MoEF&CC/6589 19th August, 2021

The Director Ministry of Environment, Forest & Climate Change, 4th Floor, E&F Wing, Kendriya Sadan, Koramangala, Bengaluru - 560 034

Dear Sir,

विषय Subject:- Submission of Compliance to the Environmental Clearance along with monitoring data

Please find enclosed herewith point wise compliance to the following Environmental Clearance(s)-issued to MRPL by Ministry of Environment, Forest & Climate Change (MoEF & CC), New Delhi.

1. Letter No. J-11011/6/89-IA.II dated 1st February 1991 (Phase-I Project)

Also environment monitoring data of Noise level, Base levels of Ground Water, Ground Water quality, SO₂ Emission and Ambient Air Quality for the period October, 2020 to March, 2021 is enclosed as Annexure – I to V.

धन्यवाद Thanking You,

भवदीय Yours sincerely,

मंगतर रिफाइनरी एंड पेटोकेमिकल्स लिमिटेड For Mangalore Refinery & Petrochemicals Limited,

एम.एस स्दर्शन M.S Sudarsan

मुख्य महा प्रबंधक (स्वास्थ्य, संरक्षा एवं पूर्यावरण)

Chief General Manager (Health, Safety and Environment)

Encl: As above

Cc: Zonal Office, CPCB, Bengaluru Head Office, KSPCB, Bengaluru Regional Office, KSPCB, Mangaluru

बेंगलूरु कार्यालय : प्लाट नं. A-1, - के .एस.एस.आई.डी.सी. प्रशासनिक कार्यालय भवन के सामने, इंडस्ट्रीयल एस्टेट, राजाजीनगर, बेंगलूरु -560 010

Bengaluru Office: Plot A-1, Opp. KSSIDC A. O. Building, Industrial Estate, Rajajinagar, Bengaluru - 560 010.

दूरभाष : Tel: (का.) (O) 080-22642200, फैक्स Fax : 080 - 23505501

दिल्ली कार्यालय : कोर-8,7वीं मंजिल, स्कोप कांप्लेक्स, लोधी रोड, नई दिल्ली- 110003 दूरभाष: 011-24306400, फैक्स: 011-24361744 : Core-8,7th, Floor SCOPE Complex, Lodhi Road, New Delhi - 110003. Tel.: 011-24306400, Fax: 011-24361744 : मेकर टॉवर 'ई' विंग 15वां तल, कफ परेड, मुबंई - 400 005. दूरभाष: 022-22173000, फैक्स: 22173233 Delhi Office

Mumbai Office : Maker Tower, 'E' Wing, 15th Floor, Cuffe Parade, Mumbai-400 005. Tel.: 022-22173000, Fax: 22173233

Page 1 of 13

Compliance to the Environmental Clearance for setting up New Refinery at Mangalore issued by Ministry of Environment, Forest & Climate Change, New Delhi

Letter No. J-11011/6/89-IA.II dated 1st February 1991

SI. No.	Stipulation	Compliance
1.	The Project authority must strictly adhere to the stipulations made by the State Pollution Control Board and the State Government and a comprehensive EIA will be submitted within 18 months.	KSPCB stipulations being adhered to.
2	Any expansion of the plant, either with the existing product mix or new products can be taken up only with the prior approval of this Ministry.	Noted and being followed. Any expansion of the plant either with the existing product mix or new products will be taken up only with the prior approval of this Ministry.
3	The gaseous emissions from various process units should conform to the standard prescribed by the concerned authorities from time to time. At no time, the emission level should go beyond the stipulated standards. In the event of failure of any pollution control system adopted by the unit, the respective unit should be put out of operation immediately and should not be restarted until the control measures are rectified to achieve the desired efficiency.	Noted & being complied. The gaseous emission from various process units is conformed to the standard prescribed by the concerned authorities from time to time.
4	Adequate number (a minimum of 5) of air quality monitoring stations should be set up in the downwind direction as well as where maximum ground level concentration is anticipated. Also, stack emission should be monitored by setting up of automatic stack monitoring unit. The data on stack emission should be submitted to State Pollution Control Board once in three months and to this Ministry once in six months along with the statistical analysis. The air quality monitoring station should be selected on the basis of modelling exercise to represent the short-term ground level concentration.	Complied. Total 10 nos. AAQ stations are installed in consultation with KSPCB and readings are being submitted to the Board regularly. Data on stack emission being submitted to State Pollution Control Board once in three months and to this Ministry once in six months along with the statistical analysis. Online Analyzers are provided in all major stacks attached to various heaters. The online data is being



		continuously transferred to CPCB and KSPCB.
5	There should be no change in the stack design without approval of State Pollution Control Board. Alternate Pollution Control System and proper design (Steam injection system) the stack should be provided to take care of excess emission due to failure in any system of the plant	Noted and complied
6	The project authority should recycle the waste to the maximum extent. The recycling plan should be submitted within one year. Liquid effluent coming out of plants should meet the stipulated standards and disposed only into the identified outfall point in the sea as recommended in the NIO study after using for green belt development to the maximum extent possible.	Treated effluent being recycled to cooling towers to the maximum extent and balance is discharged to sea through a submarine pipeline of 650 m length and at 6.5 m depth as identified by NIO. A standby pipeline also provided for any contingency.
		Healthiness of the Submarine Pipeline is being monitored by M/s. NIO every year.
7	Adequate number of effluent quality monitoring stations must be set up in consultation with the State Pollution Control Board and the effluents monitored, and, should be statistically analysed and the report sent to this Ministry one in six months and to the Pollution Control Board once in three months. If the effluent quality at any time, exceeds the standards prescribed, the corresponding units of the plant which are contributing to the excessive pollutant load shall be immediately stopped from operation till the quality of pollutants discharged from the units are brought down to the required level.	Complied. Daily analysis reports are being submitted to KSPCB on monthly basis. Also, Treated effluent from APMC yard is monitored and analysis reports are submitted to KSPCB on monthly basis. In addition M/s. Central Marine Fisheries Research Institute (CMFRI), Mangalore is monitoring at 10 stations (7 inside the sea at Marine Outfall Point + 3 on the shore) on fortnightly basis. No adverse effects on the marine ecosystem observed till date.
		Online Continuous Monitoring stations installed for monitoring



		treated effluent as per CPCB guidelines.
8	The project authority should prepare a well-designed scheme for solid waste disposal generated during various processes operation or in treatment plant. The plan for disposal should be submitted to the Ministry within six months.	MRPL have reduced
		MRPL has designed a system for reprocessing of oily sludge in Delayed Coking Unit (DCU). Apart from this, we have installed an advanced Closed Bioremediation unit which helps in bioremediation of oily sludge in phased manner.
		Further, Oily sludge is being disposed to Cement Industries for Co-processing in their unit.
9	An ecological study at the marine outfall point should be initiated immediately and report submitted within three years. The terms of reference of this study should be finalised in consultation with this Ministry.	Complied.
10	The project authority will relocate residential complexes in keeping with the State Government stipulations and will prepare a well designed township for displaced persons and will submit within six months to this Ministry for review.	The rehabilitation colony has developed at Chelairu village and all project evacuees have been accommodated there.
11	The project proponent must take up with the Government of Karnataka for restriction urban sprawl and growth of ancillaries and growth of informal sector within 5 KMS of project site. A master plan must be submitted within one year.	Complied
12	The project authority will submit to this ministry for review a well designed plan for afforestation in the hill slopes of plateau within six months and will afforest all vacant lands which are not used for plant utility. The land shown for further expansion must also be afforested in consultation with Forest Department. The minimum tree density should be 1000 per acre. A detailed green belt plan which interalia including type	Complied



2/63

	of plants, plantations schedule and a monitoring programme (preferably with physical inspection every six month) and indicating milestones on a PERT CHART should be submitted to this department within six months.	
13	The project authorities will maximise the use of well designed pipeline for the transport of input material and finished product to avoid road congestion.	All the input and output materials are transported by well designed pipelines.
14	A detailed risk analysis based on Maximum Credible accident analysis should be done once the process design and lay-out is frozen. Based on this a disaster management plan has to be prepared and after approval by the concerned nodal agency, should be submitted to this Ministry within six months.	Prepared & Submitted.
15	The project authority must set up a laboratory facility for collection and analysis of samples under the supervision of competent technical personnel who will directly report to the Chief Executive.	A well established NABL Accredited Laboratory has set up and functioning in the Refinery.
16	A separate environmental management cell with suitably qualified people to carry out various functions should be set up under the control of senior executive who will report directly to the head of the organisation	MRPL is having a separate Environment Management Cell headed by Chief General Manager (CGM) and having required laboratory infrastructure earmarked for Environmental cell activities.
17	The funds earmarked for the environmental protection measures should not be diverted for other purposes and year-wise expenditure should be reported to this Ministry.	Complied
II	The Ministry or any other competent authority may stipulate any further condition after reviewing the comprehensive impact assessment report or any other reports prepared by project authorities.	Noted.
III	The Ministry may revoke clearance if implementation of the conditions is not satisfactory	Noted.
IV	The above conditions will be forced inter-alia along with the Water (Prevention & Control of Pollution) Act, 1974, Air (Prevention & Control of Pollution) Act, 1981 and Environment (Protection) Act, 1986, along with their amendments.	Noted.



1

ANNEXURE - I

AVERAGE MONTHLY EXTRACT OF NOISE LEVEL (IN dB) AROUND REFINERY


MONTH	BOUNDARY WALL NORTH OF THE REFINERY	BOUNDARY WALL SOUTH OF THE REFINERY	BOUNDARY WALL EAST OF THE REFINERY	BOUNDARY WALL WEST OF THE REFINERY
Oct-20	53.7	58.6	58.1	60.4
Nov-20	55.4	60.8	52.8	57.5
Dec-20	57.5	64.8	52.3	63.9
Jan-21	53.6	53.6	53.9	50.9
Feb-21	58.5	69.3	54.9	71.5
Mar-21	46	55	51	55



Water
parent .
of Ground
0
995)
e (Period 1
s value
Levels
Base

		100	Westbothun	Valariar	Kalayar	Kalavar	lokatte	lokatte	Jokatte	Malyapada	Malyapada	Malyapada
Parameter/Location	Kuthethur	Kuthethur	Vacileural	Manavai	(minter)	(summer)	(Monsoon)	(winter)	(summer)	(Monsoon)	(winter)	(summer)
/	Monsoon	winter	Summer	Timonsoon)	T ANTITICE I	7.6	8.1	α r.	7.8	7	7.7	8.1
hd	8.2	8	8.3	/.1		0.1	1.5	200	0 % C	70	300	106
Conductivity (uS)	220	630	70	09	300	70	100	079	740	0/	300	201
The name	121	284	30	28	154	45	88	341	127	30	210	23
1DS, ppin	177		200	-	-	2	-	8	33	0.2	0	1.1
Turbidity (NTU)	17	1	000	1 11	VIV	NIA VIA	NA	NA	NA	AN	NA	NA
p-alkalinity, ppm	AN	AN	NA	V.	IA.	. Var	500	116	7.4.	23	30	50
M-alkalinity, ppm	80	130	108	10	30	α	79	110	1		700	63
Total Handnord nam	70.4	100	84	10.8	100	44	87	105	115	23.4	100	70
Total naturiess ppm	100		V V	101	20	13	50.3	85	78	18.8	30	31
Ca Hardness ppm	40.7	nc	+	10.1			27	00	11	α	40	18
Chloride ppm	11	45	10	10	38	ΩĪ	17	00	1		GIN	GN
	CZ	dN	CIN	QN	QN	ND	QN	QN	ON	ND	UND	avi.
Pnenoi ppm	OK.	a.		0.00	C Z	0.003	0.013	GN	0.071	0.007	ON	ND
Iron ppm	0.154	ON	0.24	0.010	GN.	0.043	270.0	4	r	-	CIN	CIN
Conner micro am/l	ON	QN	QN	,4	QN	2	1	QN	2	-	ON!	
Zime a sum a day	1,0051	CN	QN	0.024	ND	QN	0.02	QN	ND	0.183	ON	N
Zinc ppm	0.001	VIV	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ΔN	AN	AZ	NA	NA	NA	AN	NA	AN
Arsenic, Micro gm/1	INA	VVI	UM	TATA		92	GN	QN	CN	CZ	QN	QN
Lead micro gm/l	QN	ON	QN	QN	N.C.	QN.	QNI	Q.			CN	CX
Chromium micro gm/1	. 11	ON	ON	15	QN	QN	14	0.7	ON:	01	2	CN CN
Oil pam	O.N.	QN	QN	QN	QN	QN.	ND	QN	ND	ND	IND	Casa
mdd IIO	2 22	747										

NA - Not applicable



SA / ESS

Parameters	D'souza Well	Fernandes Well	Hand Bore	HGIL Bore 5	HGIL Bore	MD Bunglow	SRU-II
рН	6.6	6.5	6.4	6.4	6.7	6.7	6
T-Hardness, ppm	28	20	. 60	70	80	70	36
Ca-Hardness, ppm	16	18	40	38	42	62	24
Mg-Hardness, ppm	12	2	20	32	38	8	12
Chloride,ppm	15.9	13.6	49	54	55	12	26
Sulphate,ppm	30	19	25	20	14	18	12.9
Fluoride, ppm	<0.1	<0.1	< 0.1	<1.0	<1.0	<0.1	< 0.1
Iron, ppm	<1.0	0.56	0.6	0.2	0.52	< 0.1	1.9
Nitrate, ppm	76	<1.0	1.1	1.6	10.6	<1.0	<1.0
TDS, ppm	<0.1	77	255	276	275	82	118
Phenol, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Lead, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Cadmium, ppm	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1
Hexavalent Chromium, ppm	< 0.1	<0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1
Copper, ppm	<0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Zinc, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Nickel, ppm	<0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Manganese, ppm	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Total Chromium, ppm	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03
COD,ppm	42	26	105	68	57	10	48
Oil, ppm	<1.0	<1.0	6	3	4.5	< 0.1	6.5
Appearance	Clear	Clear	Muddy	Muddy	Muddy	Clear	Muddy
Odour	Odourless	Odourless	HC	НС	нс	Odourless	Odourless

GROUND WATER MONITORING REPORT FOR THE MONTH OF OCTOBER-2020

Sampling not done due to COVID-19 as KSPCB offical not come for sampling

GROUND WATER MONITORING REPORT FOR THE MONTH OF November-2020

Sampling not done due to COVID-19 as KSPCB offical not come for sampling

Parameters	D'souza Well	ETP-2 Bore	Fernandes Well	Hand Bore	Kalavar Church	MD Bunglow	SRU-II
pH	6.1	5.7	5	7.1	6.2	7.2	5.6
T-Hardness, ppm	48	54	52	86	44	50	60
Ca-Hardness, ppm	20	22	16	46	10	26	30
Mg-Hardness, ppm	28	32	36	40	34	24	30
Chloride,ppm	49.5	5.1	45.1	56	32.9	11.1	3
Sulphate,ppm	22.9	6.5	25.1	6	3.3	11.8	1.1
Fluoride, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Iron, ppm	0.38	1.7	0.23	0.24	0.73	0.14	2.3
Nitrate, ppm	<1.0	<1.0	1.5	<1.0	28.3	<1.0	<1.0
TDS, ppm	136	144	129	311	134	64	143
Phenol, ppm	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1
Lead, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Cadmium, ppm	<0.1	< 0.1	<0.1	<0.1	<0.1	< 0.1	< 0.1
Hexavalent Chromium, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Copper, ppm	< 0.1	<0.1	<0.1	< 0.1	<0.1	<0.1	< 0.1
Zinc, ppm	< 0.1	<0.1	< 0.1	<0.1	< 0.1	<0.1	< 0.1
Nickel, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Manganese, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Total Chromium, ppm	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03
COD,ppm	10	56	28	48	22	10	48
Oil, ppm	<1.0	2	<1.0	3	<1.0	<1.0	2
Appearance	Clear	Muddy	Clear	Muddy	Clear	Clear	Muddy
Odour	Odourless	Odourless	Odourless	HC	Odourless	Odourless	Odourless



54 155

	GROUND WAT	TER MONITOR	ING REPORT FO	OR THE MONTI	l OF JANUAR	Y-21		
Parameters	D'souza Well	Fernandes Well	Hand Bore	HGIL Bore 5	HGIL Bore	Kalavar Church	MD Bunglow	SRU-II
рН	6.1	6.1	7.1	6.1	6	5.2	7.2	5.9
T-Hardness, ppm	38	46	52	30	38	32	32	40
Ca-Hardness, ppm	18	26	36	14	18	20	24	30
Mg-Hardness, ppm	20	20	16	16	20	12	8	10
Chloride,ppm	59	26	60	29	27	40	13.8	34
Sulphate,ppm	16.8	ND	ND	ND	ND	ND	ND	ND
Fluoride, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Iron, ppm	0.15	< 0.1	3.2	8.5	14	0.41	< 0.1	12.7
Nitrate, ppm	6.4	1.6	<1.0	<1.0	<1.0	20.6	< 1.0	< 1.0
TDS, ppm	133	133	289	115	144	127	58	148
Phenol, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Lead, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Cadmium, ppm	<0.1	<0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1
Hexavalent Chromium, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Copper, ppm	<0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1
Zinc, ppm	< 0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	<(),1
Nickel, ppm	<0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	<:0.1
Manganese, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< (), 1
Total Chromium, ppm	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	<0.03
COD,ppm	81	37	44	81	72	41	56	51
Oil, ppm	<1.0	<1.0	14	19	18	<1.0	<1.0	6.5
Appearance	Clear	Clear	Muddy	Muddy	Muddy	Clear	Clear	Muddy
Odour	Odourless	Odourless	НÇ	Odourless	Odourless	Odourless	Odourless	Odourless

- GR	OUND WATER MO		PORTFORTAL	MONTHOFFE			
Parameters	D'souza Well	Fernandes Well	Hand Bore	HGIL Bore 5	HGIL Bore 6	MD Bunglow	Kalavar Church
pH	6.6	6.8	8.2	6.8	7	8.2	7.2
T-Hardness, ppm	44	64	40	50	40	32	<1.0
Ca-Hardness, ppm	30	38	30	24	32	26	10
Mg-Hardness, ppm	14	26	10	26	8	6	34
Chloride,ppm	41	43	43	43	22	15.5	25
Sulphate,ppm	27	17.6	13.5	15.7	8.8	14.3	12.3
Fluoride, ppm	< 0.1	<0.1	2.2	< 0.1	< 0.1	<0.1	< 0.1
Iron, ppm	0.16	1.4	8.2	10	14.1	0.24	1.4
Nitrate, ppm	1	2.6	<1.0	<1.0	1.2	1.1	29
TDS, ppm	162	209	262	145	150	73	135
Phenol, ppm	<0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1
Lead, ppm	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Cadmium, ppm	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Hexavalent Chromium, ppm	<.0.1	< 0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1
Copper, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1
Zinc, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Nickel, ppm	<0.1	<0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1
Manganese, ppm	<0.1	<0.1	< 0.1,	< 0.1	< 0.1	< 0.1	< 0.1
Total Chromium, ppm	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03	< 0.03
COD,ppm	24	20	48	34	20	24	87
Oil, ppm	<1.0	<1.0	13	7	4.5	5	<1.0
Appearance	Clear	Clear	Muddy	Muddy	Muddy	Clear	Clear
Odour	Odourless	Odourless	Odourless	HC	HĊ	Odourless	Odourless



Mark from

GI	ROUND WATER N	MONITORING R	EPORT FOR T	HE MONTH OF	MARCH-21		
Parameters	D'souza Well	Fernandes Well	Hand Bore	HGIL Bore 5	HGIL Bore 6	Kalavar Church	MD Bunglow
рН	6.1	5.8	6.5	6.6	6.5	5.5	7.6
T-Hardness, ppm	52	36	54	64	64	38	40
Ca-Hardness, ppm	30	14	38	36	40	12	28
Mg-Hardness, ppm	22	22	16	28	24	26	12
Chloride,ppm	38	31	18	18	39	31	14.5
Sulphate,ppm	20.3	10.9	15.7	8.4	11.4	9.8	13.5
Fluoride, ppm	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Iron, ppm	0.1	< 0.1	10.1	8.9	9.8	0.1	0.21
Nitrate, ppm	1.3	6.3	<1.0	<1.0	<1.0	21.9	<1.0
TDS, ppm	152	103	185	195	187	119	63
Phenol, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Lead, ppm	< 0.1	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Cadmium, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Hexavalent Chromium, ppm	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1	< 0.1
Copper, ppm	<0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Zinc, ppm	< 0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	<().1
Nickel, ppm	< 0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1
Manganese, ppm	<0.1	< 0.1	< 0.1	< 0.1	<0.1	< 0.1	< 0.1
Total Chromium, ppm	< 0.03	<0.03	< 0.03	< 0.03	<0.03	< 0.03	< 0.03
COD,ppm	49	24"	29	29	20	20	29
Oil, ppm	<1.0	<1.0	2	4.5	2	3.5	-3
Appearance	Clear	Clear	Muddy	Muddy	Muddy	Clear	Clear
Odour	Odourless	Odourless	Odourless	HC	Odourless	Odourless	Odourless



. 8

Annexuse-IV

Total SO₂ Emission from the Plant (Through Stacks)

MONTH	Total SO ₂ Emission (TPD)
Oct-20	36.20
Nov-20	37.60
Dec-20	31.20
Jan-21	27.10
Feb-21	31.20
Mar-21	29.50

Note: TPD - Tonnes per Day

Additional SO₂ Emission through flaring as follow;

MONTH	Total SO ₂ Emission (TPD)
Oct-20	9.7
Nov-20	10.0
Dec-20	22.7
Jan-21	18.0
Feb-21	11.6
Mar-21	11.6

Note: TPD - Tonnes per Day



Ambient Air Quality Monitoring Data for October- 2020

LOCATION	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	CO	O_3 $\mu g/m^3$
LOCATION	μg/m ³	μg/m ³	μg/m ³	μg/m ³	mg/m ³	
Permude	12.1	15.1	27	19	BDL	BDL
Perara	12.2	15.6	26	18	BDL	BDL
Ganeshpura	12.6	15.8	30	18	BDL	BDL
Cooling Tower	12.9	16.7	27	19	BDL	BDL
ETP	14.3	18.5	25	17	BDL	BDL
Benkinatheswara Temple	12.3	14.5	35	21	BDL	BDL
Substation - 45 area	13.2	16.2	33	20	BDL	BDL
Near CL area Weighbridge	12.1	14.8	39	26	BDL	BDL
Substation - 40 area	13.4	16.9	31	20	BDL	BDL
CISF Quarters	10.5	12.1	22	16	BDL	BDL

BDL: Below Detectable Limit

Ambient Air Quality Monitoring Data for November - 2020

LOCATION	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	СО	03
LOCATION	μg/m ³	μg/m³	μg/m ³	μg/m³	mg/m ³	μg/m³
Permude	12.3	15.4	30	22	BDL	BDL
Perara	12.3	15.8	28	20	BDL	BDL
Ganeshpura	12.6	16.2	36	23	BDL	BDL
Cooling Tower	13.2	16.9	30	21	BDL	BDL
ETP	14.3	18.6	29	21	BDL	BDL
Benkinatheswara Temple	12.4	14.8	37	23	BDL	BDL
Substation - 45 area	12.9	16.3	35	22	BDL	BDL
Near CL area Weighbridge	12.5	15.0	40	27	BDL	BDL
Substation - 40 area	13.5	17.2	33	22	BDL	BDL
CISF Quarters	11.0	12.4	25	19	BDL	BDL

BDL: Below Detectable Limit

Ambient Air Quality Monitoring Data for December - 2020

LOCATION	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	BDL BDL BDL BDL BDL BDL BDL BDL BDL	O_3 $\mu g/m^3$
LOCATION	μg/m ³	μg/m ³	μg/m ³	μg/m ³		
Permude	12.7	15.9	32	24		BDL
Perara	12.9	16.2	31	21	BDL	BDL
Ganeshpura	13.2	16.7	36	24	BDL	BDL
Cooling Tower	13.4	17.1	31	23	BDL	BDL
ETP	14.6	18.8	31	22	BDL	BDL
Benkinatheswara Temple	12.9	15.0	37	24	BDL	BDL
Substation - 45 area	13.4	16.7	36	24	BDL	BDL
Near CL area Weighbridge	12.8	15.4	41	28	BDL	BDL
Substation - 40 area	13.6	17.4	34	23	BDL	BDL
CISF Quarters	11.3	12.7	28	20	BDL	BDL

BDL: Below Detectable Limit



35 m

Ambient Air Quality Monitoring Data for January - 2021

L O CARRON	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	BDL BDL BDL BDL BDL BDL BDL	O_3
LOCATION	μg/m ³	μg/m ³	μg/m ³	μg/m³		μg/m³
Permude	13.0	16.2	34	25	BDL	BDL
Perara	13.1	16.5	32	22	BDL	BDL
Ganeshpura	13.5	17.0	37	25	BDL	BDL
Cooling Tower	13.7	17.4	32	24	BDL	BDL
ETP	14.9	19.1	32	23	BDL	BDL
Benkinatheswara Temple	13.2	15.3	39	25	BDL	BDL
Substation - 45 area	13.7	17.0	37	25	BDL	BDL
Near CL area Weighbridge	13.1	15.7	42	29	BDL	BDL
Substation - 40 area	13.9	17.7	35	25	BDL	BDL
CISF Quarters	11.6	13.1	30	21	BDL	BDL

BDL: Below Detectable Limit

Ambient Air Quality Monitoring Data for February - 2021

A OCATION	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	CO	O_3 $\mu g/m^3$
LOCATION	μg/m ³	μg/m³	μg/m³	μg/m ³	mg/m ³	
Permude	13.1	16.3	34	26	BDL	BDL
Perara	13.2	16.7	33	23	BDL	BDL
Ganeshpura	13.6	17.1	38	26	BDL	BDL
Cooling Tower	14.0	17.8	33	25	BDL	BDL
ETP	15.0	19.4	33	24	BDL	BDL
Benkinatheswara Temple	13.3	15.6	39	26	BDL	BDL
Substation - 45 area	13.8	17.2	38	26	BDL	BDL
Near CL area Weighbridge	13.3	15.9	43	30	BDL	BDL
Substation - 40 area	14.3	18.1	37	26	BDL	BDL
CISF Quarters	11.9	13.3	31	23	BDL	BDL

BDL: Below Detectable Limit

Ambient Air Quality Monitoring Data for March-2021

	SO ₂	NO ₂	PM ₁₀	PM _{2.5}	CO	O_3
LOCATION	μg/m ³	μg/m³	μg/m ³	μg/m³	BDL	μg/m ³
Permude	13.6	16.7	36	27	BDL	BDL
Perara	13.7	17.2	34	25	BDL	BDL
Ganeshpura	14.1	17.6	40	27	BDL	BDL
Cooling Tower	14.3	18.0	34	26	BDL	BDL
ETP	15.4	19,7	34	25	BDL	BDL
Benkinatheswara Temple	13.8	15.8	40	27	BDL	BDL
Substation - 45 area	14.3	17.6	39	27	BDL	BDL
Near CL area Weighbridge	13.6	16.3	44	31	BDL	BDL
Substation - 40 area	14.4	18.3	38	27	BDL	BDL
CISF Quarters	12.2	13.7	32	23	BDL	BDL

BDL: Below Detectable Limit



3 7 002